

[Home](#) > [Products](#) > > [960009](#) > [960009CFLFT](#)
[Add to myIDT \[?\]](#)

You may also like...


960009CFLFT

Category:
Generic Part: 960009

Market Group: PC CLOCK

Description: PC SPECIAL PURPOSE

Output Features: $\hat{\epsilon}$ ASIC power 2.5V - 3.3V $\hat{\epsilon}$ Supports Spread Spectrum $\hat{\epsilon}$ 1 - Single-ended CPU $\hat{\epsilon}$ 5 - Pair Differential DDR outputs $\hat{\epsilon}$ 9 - PCI outputs $\hat{\epsilon}$ 1 - ASIC @ 33MHz $\hat{\epsilon}$ 1 - ASIC @ 80MHz - 100MHz
 Features/Benefits: $\hat{\epsilon}$ Selectable I2C address $\hat{\epsilon}$ Selectable output enable/disable via I2C $\hat{\epsilon}$ CPU - DDR skew typically <150ps Key Specifications: $\hat{\epsilon}$ CPU jitter: <150ps $\hat{\epsilon}$ PCI skew: <



Parameters

| | |
|-------------------------|-----------------|
| Package | SSOP 48 (PVG48) |
| Speed | NA |
| Temperature | C |
| Voltage | 3.3 V |
| Status | Active |
| Sample | No |
| Minimum Order Quantity | 1000 |
| Factory Order Increment | 1000 |

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

| Type | Title | Size | Revision Date |
|------|------------------------|-------|---------------|
| Misc | PC Clocks Contact Info | 61 KB | 05/29/2007 |

Package

| | |
|----------------------------------|--------------------------|
| Description | SSOP 300 MIL, 48LD |
| Class | PLASTIC |
| Moisture Sensitivity Level (MSL) | 1 |
| Category | Green |
| Moisture Exposure Floor Life | Unlimited @ <30°C/85% RH |
| Peak Reflow Temperature | 260°C |
| Rebake Conditions | NA |
| Length | 15.9 |
| Mark | PVG |
| Width | 7.5 |
| Pitch | 0.64 |
| Thickness | 2.3 |
| Status | Active |