

[Home](#) > [Products](#) > > 960008 > 960008AFLF

[Add to myIDT \[?\]](#)

You may also like...

## 960008AFLF

**Category:**
**Generic Part:** 960008

**Market Group:** PC CLOCK

**Description:** PC SPECIAL PURPOSE

Recommended Application: Ricoh Printer Application (Soriano) Output Features:  $\hat{\text{a}}\text{€}\phi$  2.5V - 3.3V power for GIGA/ASIC  $\hat{\text{a}}\text{€}\phi$  Supports Spread Spectrum  $\hat{\text{a}}\text{€}\phi$  1 - Single-ended GIGACLK @ 125MHz  $\hat{\text{a}}\text{€}\phi$  1 - ASIC @ 33MHz  $\hat{\text{a}}\text{€}\phi$  1 - ASIC @ 80MHz - 133MHz  $\hat{\text{a}}\text{€}\phi$  1 - SDCLK @ 50MHz Features/Benefits:  $\hat{\text{a}}\text{€}\phi$  Selectable SMBus address  $\hat{\text{a}}\text{€}\phi$  Selectable output enable/disable via SMBus Key Specifications:  $\hat{\text{a}}\text{€}\phi$  Clock jitter: <250ps  $\hat{\text{a}}\text{€}\phi$  Operating current: <50mA (typical)

**Parameters**

Package	SSOP 28 (PYG28)
Speed	NA
Temperature	C
Voltage	3.3 V
Status	Active
Sample	Yes
Minimum Order Quantity	94
Factory Order Increment	47

**Distributor Inventory**

No Pricing information is available from our Distributors at this time.

**Documents**

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

**Package**

Description	SSOP 5.3 MM
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Green
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	260°C
Rebake Conditions	NA
Length	10.2
Mark	PYG
Width	5.3
Pitch	0.65
Thickness	1.73
Status	Active