

[Home](#) > [Products](#) > > [952911](#) > [952911BFLF](#)
[Add to myIDT \[?\]](#)

You may also like...


## 952911BFLF

**Category:**
**Generic Part:** 952911

**Market Group:** PC CLOCK

**Description:** PC MAIN CLOCK

ICS952911 is a 48 pin clock chip for VIA PT890 style chipsets. When used with a fanout DDR buffer, such as the 93788, it provides all the necessary clock signals for such a system. Output Features:  $\phi$  2 - 0.7V current-mode differential CPU pairs  $\phi$  10 - PCI, 3 free running, 33MHz  $\phi$  3 - REF, 14.318MHz  $\phi$  3 - 3V66, 66.66MHz  $\phi$  1 - 48MHz  $\phi$  1 - 24/48MHz  $\phi$  2 - 25MHz @ 2.5V



### Parameters

Package	SSOP 48 (PVG48)
Speed	NA
Temperature	C
Voltage	3.3 V
Status	Active
Sample	Yes
Minimum Order Quantity	120
Factory Order Increment	30

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

### Package

Description	SSOP 300 MIL, 48LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Green
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	260°C
Rebake Conditions	NA
Length	15.9
Mark	PVG
Width	7.5
Pitch	0.64
Thickness	2.3
Status	Active